

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS







Printing date 15.11.2012

Revision: 30.04.2017

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Oil Checker
- **Article number:** 16501
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation** Oil Identification/Oil Additive
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Highside Chemicals, Inc.
11114 Reichold Road
Gulfport, MS 39503
Phone: (228) 896-9220
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- | | |
|---|---|
|  | GHS02 flame |
| Flam. Liq. 2 | H225 Highly flammable liquid and vapour. |
- | | |
|---|--------------------------------------|
|  | GHS05 corrosion |
| Eye Dam. 1 | H318 Causes serious eye damage. |
- | | |
|---|---|
|  | GHS07 |
| Acute Tox. 4 | H302 Harmful if swallowed. |
| Skin Irrit. 2 | H315 Causes skin irritation. |
| STOT SE 3 | H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. |
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
- | | |
|---|-----------------------|
|  | Xn; Harmful |
| R22: | Harmful if swallowed. |
- | | |
|---|--|
|  | Xi; Irritant |
| R37/38-41: | Irritating to respiratory system and skin. Risk of serious damage to eyes. |
- | | |
|---|---------------------|
|  | F; Highly flammable |
|---|---------------------|

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 1)

R11: Highly flammable.

R67: Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

butan-1-ol

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 Wear protective gloves and eye protection.

P233 Keep container tightly closed.

P261 Avoid breathing mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 2)

- **Hazard description:**
- **WHMIS-symbols:**
B2 - Flammable liquid
D2B - Toxic material causing other toxic effects



- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **HMIS Long Term Health Hazard Substances**

64-17-5 ethanol

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6	butan-1-ol ☒ Xn R22; ☒ Xi R37/38-41 R10-67 ☒ Flam. Liq. 3, H226 ☒ Eye Dam. 1, H318 ☒ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	50-100%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5	ethanol ☒ F R11 ☒ Flam. Liq. 2, H225	25-50%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 3)

4 First aid measures

· 4.1 Description of first aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Dizziness

Coughing

Gastric or intestinal disorders

Disorientation

Breathing difficulty

· **Hazards**

Danger of pulmonary oedema.

Danger of convulsion.

Danger of impaired breathing.

Condition may deteriorate with alcohol consumption.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation.

Monitor circulation, possible shock treatment.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** None.

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 4)

Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded.
Can form explosive gas-air mixtures.
Danger of receptacles bursting because of high vapour pressure when heated.

- **5.3 Advice for firefighters**

- **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

- **6.2 Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may form in empty receptacles.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 5)

Store away from oxidizing agents.

- **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

71-36-3 butan-1-ol

PEL (USA)	300 mg/m ³ , 100 ppm
REL (USA)	Short-term value: C 150 mg/m ³ , C 50 ppm Skin
TLV (USA)	61 mg/m ³ , 20 ppm
EL (Canada)	Short-term value: C 30 ppm Long-term value: 15 ppm
EV (Canada)	20 ppm

64-17-5 ethanol

PEL (USA)	1900 mg/m ³ , 1000 ppm
REL (USA)	1900 mg/m ³ , 1000 ppm
TLV (USA)	Short-term value: 1880 mg/m ³ , 1000 ppm
EL (Canada)	Short-term value: 1000 ppm
EV (Canada)	1,900 mg/m ³ , 1,000 ppm

- **DNELs** No further relevant information available.

- **PNECs** No further relevant information available.

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device when aerosol or mist is formed.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 6)

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact gloves made of the following materials are suitable:**

Butyl rubber, BR
Nitrile rubber, NBR
Natural rubber, NR
Neoprene gloves

- **Eye protection:**

Contact lenses should not be worn.



Tightly sealed goggles

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Colour: Clear

· **Odour:** Alcohol-like

· **Odour threshold:** Not determined.

· **pH-value at 20 °C:** 9

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 7)

· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	171 °F / 78 °C
· Flash point:	59 °F / 15 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	644 °F / 340 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not self-igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1,5 Vol %
Upper:	15,0 Vol %
· Vapour pressure at 20 °C:	59 hPa
· Density at 20 °C:	0,79 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Flammable.
Reacts with oxidizing agents.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Used empty containers may contain product gases which form explosive mixtures with air.
Reacts with peroxides and other radical forming substances.
Strong exothermic reaction with acids.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 8)

Develops readily flammable gases/fumes.

- **10.4 Conditions to avoid**

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

- **10.5 Incompatible materials:** No further relevant information available.

- **10.6 Hazardous decomposition products:**

Hydrocarbons

Carbon monoxide and carbon dioxide

11 Toxicological information

- **11.1 Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

64-17-5 ethanol

Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Strong irritant with the danger of severe eye injury.

- **Sensitization:** No sensitizing effects known.

- **Subacute to chronic toxicity:**

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

- **Acute effects (acute toxicity, irritation and corrosivity)** Vapours have narcotic effect.

- **Repeated dose toxicity** May cause damage to organs through prolonged or repeated exposure .

12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 9)

- **Additional ecological information:**

- **General notes:**

This statement was deduced from the properties of the single components.

Avoid transfer into the environment.

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Contact waste processors for recycling information.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

- **14.1 UN-Number**

- **DOT, ADR, IMDG, IATA**

UN1987

- **14.2 UN proper shipping name**

- **DOT, IATA**

- **ADR**

ALCOHOLS, N.O.S. (ETHANOL, BUTANOLS)

1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), BUTANOLS)

- **IMDG**

ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), BUTANOLS)

- **14.3 Transport hazard class(es)**

- **DOT**



- **Class**

3 Flammable liquids.

(Contd. on page 11)

Safety Data Sheet



according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 10)

· Label	3
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· DOT, ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D/E
· UN "Model Regulation":	UN1987, ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), BUTANOLS), 3, II

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 11)

· Section 313 (Specific toxic chemical listings):	
71-36-3	butan-1-ol

· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	

· Proposition 65 (California):	
All ingredients are listed.	

· Chemicals known to cause cancer:	
None of the ingredients is listed.	

· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	

· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	

· Chemicals known to cause developmental toxicity:	
Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product.	

64-17-5	ethanol
---------	---------

· Carcinogenic Categories	

· EPA (Environmental Protection Agency)		
71-36-3	butan-1-ol	D

· IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	

· TLV (Threshold Limit Value established by ACGIH)		
64-17-5	ethanol	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

· Canada	

· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	

· Canadian Ingredient Disclosure list (limit 0.1%)	
64-17-5	ethanol

· Canadian Ingredient Disclosure list (limit 1%)	
71-36-3	butan-1-ol

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	
--	--

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 15.11.2012

Revision: 30.04.2017

Trade name: Oil Checker

(Contd. of page 12)

· Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

R10 Flammable.
R11 Highly flammable.
R22 Harmful if swallowed.
R37/38 Irritating to respiratory system and skin.
R41 Risk of serious damage to eyes.
R67 Vapours may cause drowsiness and dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

· Sources

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com

