

# **SAFETY DATA SHEET**

# SECTION 1) IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product ID: 54016

**Product Name:** Orange Pan Potion Resin

Revision Date: May 11, 2023 Date Printed: May 11, 2023

Version: 1.0 Supersedes Date: N.A.

Manufacturer's Name: Highside Chemicals, Inc.

Address: 11114 Reichold Rd. Gulfport, MS 39503

Emergency Phone: ChemTel Inc. (800)255-3924, +1 (813)248-0585

Information Phone Number: 228-896-9220

Fax:

Product/Recommended Uses:

# **SECTION 2) HAZARDS IDENTIFICATION**

# Classification

Eye Irritation - Category 2A

Skin Irritation - Category 2

Skin Sensitizer - Category 1

Acute aquatic toxicity - Category 2

Chronic aquatic toxicity - Category 2

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

### **Pictograms**





### Signal Word

Warning

#### Hazardous Statements - Health

H319 - Causes serious eye irritation

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

# **Hazardous Statements - Environmental**

H411 - Toxic to aquatic life with long lasting effects

### **Precautionary Statements - General**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

1

#### **Precautionary Statements - Prevention**

- P273 Avoid release to the environment.
- P264 Wash hands thoroughly after handling.
- P280 Wear protective gloves, protective clothing, eye protection/face protection.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.

### **Precautionary Statements - Response**

- P391 Collect spillage.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P302 + P352 IF ON SKIN: Wash with plenty of water.
- P321 Specific treatment (see First-Aid on this label).
- P362 + P364 Take off contaminated clothing. And wash it before reuse.
- P333 + P313 If skin irritation or a rash occurs: Get medical advice/attention.

### **Precautionary Statements - Storage**

No precautionary statement available.

### **Precautionary Statements - Disposal**

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

### Hazards Not Otherwise Classified (HNOC)

None.

	SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS		
CAS	Chemical Name	% By Weight	
proprietary	Epoxy Resin, proprietary	70% - 85%	

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

# **SECTION 4) FIRST-AID MEASURES**

### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

### **Skin Contact**

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before re-use.

### **Eye Contact**

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. If eye irritation persists: Get medical advice/attention.

#### Ingestion

Rinse mouth. Get medical attention/advice if you feel unwell. Do NOT induce vomiting unless directed by the poison control center or doctor.

### Most important symptoms/effects, acute and delayed

No data available.

# Indication of immediate medical attention and special treatment needed, if necessary

No data available.

### **SECTION 5) FIRE-FIGHTING MEASURES**

# **Suitable Extinguishing Media**

Dry chemical, foam, carbon dioxide water spray or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

### Unsuitable Extinguishing Media

High pressure water jet, Water may cause frothing.

### Specific Hazards in Case of Fire

Hazardous decomposition products formed under fire conditions.

### **Fire-fighting Procedures**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

# **Special Protective Actions**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

# **SECTION 6) ACCIDENTAL RELEASE MEASURES**

#### **Emergency Procedure**

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Do not touch or walk through spilled material.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

### Recommended Equipment

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

### **Personal Precautions**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### **Environmental Precautions**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### Methods and Materials for Containment and Cleaning up

Cover the liquid with inert absorbent. Scoop all contaminated material into containers for proper disposal. Flush area with water to remove residues.

# **SECTION 7) HANDLING AND STORAGE**

### General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

### **Ventilation Requirements**

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

#### Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

Do not cut, drill, grind, weld or perform similar operations on or near containers.

Crystalline silica may be generated when machining cured products. Overexposure may create possible cancer and silicosis hazard.

# **SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

#### **Skin Protection**

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Chemical-resistant clothing is recommended to avoid prolonged contact. Avoid unnecessary skin contact.

Wear gloves, long sleeved shirt, long pants and other protective clothing as required to minimize skin contact.

# Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Use NIOSH approved organic vapor cartridge respirator when vapor mist exposure is likely.

# **Appropriate Engineering Controls**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)
Chemical	NIOSH TWA	NIOSH STEL	NIOSH STEL	NIOSH	ACGIH TWA	ACGIH TWA	ACGIH STEL	ACGIH STEL
Name	(mg/m3)	(ppm)	(mg/m3)	Carcinogen	(ppm)	(mg/m3)	(ppm)	(mg/m3)
Chemical Name	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis	MIC	CALS	SIN	C.	

The information in this Section does not list non-hazardous components that might have relevant Basis, NIOSH TWA (mg/m3), NIOSH STEL (ppm), NIOSH STEL (mg/m3), ACGIH TWA (ppm), OSHA TWA (ppm), OSHA TWA (mg/m3), OSHA STEL (ppm), OSHA Tables (Z1, Z2, Z3), NIOSH TWA (ppm) regulatory values, if they are present at less than 100%. Please contact manufacturer for more information.

### **SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

# **Physical and Chemical Properties**

Specific Gravity	N/A
% Solids By Weight	N/A
% VOC	N/A
Appearance	N/A
Odor Description	N/A
Oddi Description	IN/A
рН	N/A N/A
•	

Flammability	N/A
Boiling Point	N/A
Evaporation Rate	N/A
Water Solubility	N/A
Vapor Density	N/A
Vapor Pressure	N/A
Auto Ignition Temp	N/A

# **SECTION 10) STABILITY AND REACTIVITY**

### Stability

Stable at normal temperature and pressure.

### **Conditions To Avoid**

Avoid contact with heat,flame,spark and other igniter. Avoid radical forming substances (metal-ions, peroxides). Uncontrolled polymerization may cause rapid evolution of heat and increase in pressure that could result in violent rupture of sealed storage vessels or containers.

# **Hazardous Polymerization**

No data available.

### Incompatibility (Materials to Avoid)

Avoid oxidizing agents, acids and bases.

### **Hazardous Decomposition Products**

Carbon monoxide, carbon dioxide and various hydrocarbons upon thermal decomposition.

# **SECTION 11) TOXICOLOGICAL INFORMATION**

### Skin Corrosion/Irritation

Causes skin irritation

# Serious Eye Damage/Irritation

Causes serious eye irritation

### Carcinogenicity

Based on available data, the classification criteria are not met.

# **Germ Cell Mutagenicity**

Based on available data, the classification criteria are not met.

# **Reproductive Toxicity**

Based on available data, the classification criteria are not met.

### Respiratory/Skin Sensitization

May cause respiratory tract irritation.

May cause an allergic skin reaction

# **Specific Target Organ Toxicity - Single Exposure**

Exposure to high concentrations of vapors may cause central nervous system effects, including headache, drowsiness, and incoordination.

Based on available data, the classification criteria are not met.

# **Specific Target Organ Toxicity - Repeated Exposure**

Based on available data, the classification criteria are not met.

### **Aspiration Hazard**

Based on available data, the classification criteria are not met.

# **Acute Toxicity**

Ingestion: May cause gastrointestinal disturbances such as nausea, vomiting, diarrhea and effects similar to those described in

inhalation. Aspiration of this product into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Based on available data, the classification criteria are not met.

# **Likely Routes of Exposure**

Inhalation, ingestion or skin absorption.

Inhalation, Ingestion, Skin contact, Eye contact

### **Potential Health Effects - Miscellaneous**

proprietary Epoxy Resin, proprietary

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guin

# **SECTION 12) ECOLOGICAL INFORMATION**

# **Toxicity**

Toxic to aquatic life

Toxic to aquatic life with long lasting effects

# Persistence and Degradability

No data available.

### **Bioaccumulative Potential**

No data available.

### Mobility in Soil

No data available.

#### Other Adverse Effects

No data available.

# **SECTION 13) DISPOSAL CONSIDERATIONS**

### Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purpose. Return drums to reclamation centers for proper cleaning and reuse.

# **SECTION 14) TRANSPORT INFORMATION**

# **U.S. DOT Information**

Status: Not regulated UN Number: N/A

Proper Shipping Name: N/A Hazard Classification: N/A Packaging group: N/A Reportable Quantity (RQ): N/A

#### **IMDG** Information

Status: Not regulated UN Number: N/A

Proper Shipping Name: N/A Hazard Classification: N/A Packaging group: N/A Reportable Quantity (RQ): N/A Marine Pollutant: No data available

#### **IATA Information**

Status: Not regulated UN Number: N/A

Proper Shipping Name: N/A Hazard Classification: N/A Packaging group: N/A Reportable Quantity (RQ): N/A

# **SECTION 15) REGULATORY INFORMATION**

CAS	Chemical Name	% By Weight	Regulation List
proprietary	Epoxy Resin, proprietary	70% - 85%	SARA312, TSCA

The information in this Section does not list non-hazardous components that might have relevant ACGIH, HAPS, OSHA, RCRA, SARA312, TSCA, CERCLA, SARA312 regulatory values, if they are present at less than 100%. Please contact manufacturer for more information.

# **SECTION 16) OTHER INFORMATION**

#### **Glossary**

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA-National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA313-Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

### Additional information (Section 3)

The specific chemical identity and/or exact percentage (Concentration) of composition has been withheld to protect confidentiality.

### Version 1.0:

Revision Date: May 11, 2023 First Edition.; First Edition.

### **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.